



Robust Powerful Cameras for all Applications

Bohr Security products provides a complete range of video surveillance products and systems. This includes IP cameras ,Analog cameras, DVRs,NVRs,etc.



In order to provide you the best security and safety Bohr offers the solutions for all the areas like airports,railway stations,traffic roads,casinos,hotels and restuar-ents,homes,office buildings,retail stores,etc.

Cameras Overview



ANALOG CAMERAS

Camera	Model	Specifications
	BAC-375	IR Waterproof Camera, 4-9mm lens (2.8-12mm is Optional), DC12V 1000mA, 36pcs F8(72pcs F5) IR LEDs, IR distance:45-55m, 3-Axis & Hide Cable bracket, color: gray and white, 1.5kgs 1/3" CCD, 700TVL 0.001lux. Also available in 650 and 550 TVL.
	BAW-375	3.6/6mm lens, 24 F5 LEDs or 36 F5 LED, IR distance: 25m, 3-Axis & Hidden Cable bracket, 0.7kg 1/3" CCD Eiffio II, 700TVL 0.001lux, OSD, 2DNR Also available in 650 and 550 TVL.
	BASGR-370	4.5" Vandalproof Dome Camera, varifocal 3.5-8mm lens DC12V, 36pcs LED, IR distance: 30m Built-in 3-Axis Bracket Size: ϕ 142x100mm; Weight:1.3kg 1/3" CCD Eiffio II, 700TVL 0.001lux, 2DNR. Also available in 650 and 550 TVL.
	BASG-370	4.5" Vandalproof Dome Camera, varifocal 3.5-8mm lens, DC12V, Built-in 3-Axis Bracket Size: ϕ 142x100mm; Weight:1.1kg 1/3" CCD Eiffio II, 700TVL 0.001lux, 2DNR.
	BALEA-370IRC	1pc 3rd generation LED Array, 60m IR Distance with 8/12/16mm lens Color 1/3 Super HAD CCDII 700TVL 0.05Lux WDR/3D DNR/Eclipse, Privacy Masking, 8X digita zoom, Mirror, OSD with IR Cut Filter(Removable IR Cut Filter)




Camera	Model	Specifications
	BAHK-H365	48pcs IR leds 50m IR Distance with 12mm Lens. Color 1/3 SUPER HAD CCD 6500TVL 0.2Lux
	BAK-SA370	3.5-8mm adjustable Lens from outside,36 pcs IR leds 30M IR Distance,Vandal proof Dome 1/3" CCD Eiffio II, 700TVL 0.001lux, 2DNR.
	BAHK-S410	24 pcs IR leds 20m IR Distance with 3.6/6mm lens Color 1/4 SHARP CCD 420TVL 0.8Lux
	BAHK-SW352	24 pcs IR leds 20m IR Distance with 3.6/6mm lens ,plastic and metal optional Color 1/3 SUPER HAD CCD 520TVL 0.2Luxv
	BAHK-B352	Color 1/3 SUPER HAD CCD ,In-door box camera B/W 1/3 CCD 600TVL 0.05Lux
	BAK-D352	Indoor box camera Color 1/3 SUPER HAD CCD 520TVL 0.3Lux

Camera	Model	Specifications
	BAHK-Z370	Strong OSD Menu,with 2D DNR Function,Move Detective Function Clear Picture in Night,Privacy Mask Function 1/3" Exview HAD CCD II 700TVLs 0.001lux/F1.2
	AK-270S	Color 1/4 SUPER HAD CCD 480TVL 0.05Lux/DSS 0.001Lux 27X optical zoom lens with 10X digital zoom,(f=3.6~97.2mm), IR CUT

IP CAMERAS

Camera	Model	Specifications
	BA-HH-T313-WDR	1/3" 1.3M Progressive Scan WDR CMOS; 0.5Lux@F1.2;CS/C Mount;H.264/MJPEG;1.3M/720p Support 1600*1200(15fps), 1280*960(25fps), 1280*720(25fps), Support Windows Mobile, Symbian, iPhone, Support WDR,DC12V1 With 2.8-12mm lens,Without power supply and bracket
	BA-HH-TR313-WDR	1/3" 1.3M Progressive Scan WDR CMOS; 0.5Lux@F1.2;CS/C Mount;H.264/MJPEG;1.3M/720p Support 1600*1200(15fps), 1280*960(25fps), 1280*720(25fps), Support Windows Mobile, Symbian, iPhone, Support WDR,15pcs IR LEDs,10M IR Distance,With IR Cut,DC12V1A With 2.8-12mm lens, Without power supply and bracket

Camera	Model	Specifications
	BA-HT320-P	<p>1/3" 2M Progressive Scan CMOS; 0.01 Lux@F1.2(Color), 0.001Lux@F1.2(B/W);CS/C Mount;H.264/MJPEG;2M/1080P, Support 1920*1080(30fps), Support Windows Mobile, Symbian,i Phone, DC12V,POE With 2.8-12mm lens, Without power supply and bracket</p>
	BA K-HT-E220	<p>1/2.5" 2M Progressive Scan CMOS; 0.5Lux@F1.2;CS/C Mount; H.264/MJPEG;2M/1080P, Main stream: 1920*1080(25fps), Sub stream:704*576(D1); Support Mobile (iPhone, Windows Mobile, BlackBerry, Symbian, Android), 20 IR LEDs, IR distance:15m,DC12V1A,IR Cut</p>
	BA-HT-XB220	<p>1/2.5" 2M Progressive Scan CMOS; 0.5Lux@F1.2; CS/C Mount;H.264/MJPEG;2M/1080P, Main stream: 1920*1080(25fps), Sub stream:704*576(D1) ; Support Mobile (iPhone, Windows Mobile, BlackBerry, Symbian, Android), 4pcs 3rd generation LED Array, 80m IR Distance, DC12V2A</p>
	BA-HT-V220	<p>1/2.5" 2M Progressive Scan CMOS; 0.5Lux@F1.2; CS/C Mount;H.264/MJPEG;2M/1080P, Main stream: 1920*1080(25fps), Sub stream:704*576(D1) ; Support Mobile (iPhone, Windows Mobile, BlackBerry, Symbian, Android), 42 IR LEDs, IR distance:30m ,DC12V1A</p>

Camera	Model	Specifications
	BA-HH-F-WDR	1/3" 1.3M Progressive Scan WDR CMOS; 0.5Lux@F1.2;CS/C Mount;H.264/MJPEG;1.3M/720p Support 1600*1200(15fps), 1280*960(25fps), 1280*720(25fps), Support Windows Mobile,Symbian,iPhone, 42pcs IR LEDs,25M IR Distance
	BA-HH-B313-W	1/3" 1.3M Progressive Scan CMOS; 0.5Lux@F1.2; CS/C Mount;H.264/MJPEG;1.3M/720p Support 1600*1200(15fps), 1280*960(25fps), 1280*720(25fps), Support Windows Mobile, Symbian,iPhone, DC12V,Wifi(802.11b/g,100M
	BA-HH-B320-P	1/3" 2M Progressive Scan CMOS; 0.01Lux@F1.2(Color),0.001Lux @F1.2(B/W);CS/C Mount;H.264/MJPEG;2M/1080P, Support 1920*1080(30fps), Support Windows Mobile,Symbian,iPhone, DC12V,POE

Video surveillance provides full visual control over a facility around the clock. With the help of digital storage you can identify people and provide evidence that a series of events has occurred. Video surveillance improves security and safety, and is used today in sectors ranging from retail to industrial complexes and other types of buildings.

BOHR Electric
 Security Systems Division
 710-415E Columbia Street,New Westminster.
 V3L 0B4.CANADA
 info@bohrelectric.com